



The name Centri already reveals it, the sound comes from a central point. Equipped with a 2-way 5" coaxial chassis, this compact loudspeaker has a very wide coverage range.

Operation is possible via any amplifier, even without DSP.

With the two monitor angles of 50° and 35°, the Centri-5 is a universal and extremely discreet sound reinforcement tool for mobile applications and in installations. The shapely housing design fits elegantly and unobtrusively into any environment.

The angled speakON connector panel can be exchanged for a connector plate with Phoenix contact plug or waterproof PG cable gland.

For flight or tripod operation and mounting in installations, various threaded points, swivel brackets and wall brackets are available.

- ✔ Plug&Play passively on any suitable amplifier, even without DSP.
- ✔ Plug&Play on the TENNAX self-powered Subwoofers (Combi-Sets).
- ✔ Plug&Play on Powersoft amplifiers with ready-to-use presets for Armonia Plus software.
- ✔ About the TENNAX (AIIDSP) 19" DSP-Controller with any suitable amplifier.

|                        |   |
|------------------------|---|
| <b>Frequency range</b> | 112 Hz - 21,5 kHz (- 10 dB)<br>150 Hz - 21 kHz (+/- 3 dB)           |
| <b>Coverage range</b>  | 90° x 90°   |
| <b>Power handling</b>  | 50 W AES / 100 W program / 200 W peak at 8 Ω                        |
| <b>Sound pressure</b>  | 106 dB SPL AES / 109 dB SPL program / 112 dB SPL peak               |
| <b>Components</b>      | 1 x 5" Coaxial Chassis  |
| <b>Connectors</b>      | 2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 1+/1- |
| <b>Dimensions</b>      | 230 (h) x 160 (w) x 177,7 mm (d)                                    |

